



## Octospense TS-30 Defoamer

CHEMICAL NAME: Polydimethylsiloxane and silica blend

PHYSICAL FORM: Aqueous nonionic emulsion

| PRODUCT SPECIFICATIONS |               | METHODS |
|------------------------|---------------|---------|
| Solids                 | 29.0 - 32.0 % | SCC-040 |
| pH                     | 7.0 - 9.5     | PHC-010 |

### PRODUCT DESCRIPTION:

Octospense TS-30 is compatible to most wet processing uses. Use either full strength or cut with water before adding, whichever gives the best dispersion into the foaming system. For starting, it is suggested that in dye becks and wash operations that 1/2 ounce of the defoamer be used per 100 gallons of the process volume. The concentration can then be adjusted to establish the most economical and efficient concentration. Octospense TS-30 is most effective when used as a preventative against foam formation; therefore, it is best to add TS-30 to the system early in the procedure.

### STORAGE AND HANDLING:

Containers should be kept tightly closed. Protect from freezing (32 deg. F.). Contents should be stirred using mechanical agitation prior to use.

The information provided herein is believed to be reliable; however, no guarantees are made or liability assumed. Tiarco Chemical makes no claims or warranties concerning the suitability of the product for a particular use or purpose.

1300 Tiarco Dr. SW; Dalton, GA 30720 USA; Tele: 706-270-5959; Fax: 706-277-9039